



SCREENSTRIP PASTE (SST007)

Main Characteristics

Product Characteristics

Paste/White cream

Instruction for use

- Ensure that the screen is completely free from ink residues remain, use Screensolve SSO038 to clean the screen.
- Rinse both sides of the screen with water and allow to drain.
- Apply Screenstrip Paste to both sides of the screen with a brush.
- Rub into the entire stencil area.
- Leave the screen for a few minutes, but do not allow product to dry.
- Wash the stencil with mains pressure water and then use a high-pressure water gun if required.
- Stubborn stains may require additional treatment with Screensolve SSO038.
- If any ink or stencil stains remain, Screenpaste & Screensolve or Chlorine should be used.
- Before the reclaimed screen is used again, it should be prepared with Degreaser P-6419.

Features

- A stencil decoating product which can be used on Nylon, Polyester and stainless steel meshes.

Standard Packing

25 Kg and 1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- SST007 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screenstrip Paste* in Safety Data Sheet.

CHAIYABOON BROTHERS CO.,LTD.

Head Office Pathumthanee 26/9 M.3 Lamukka Rd, Lamukka, Pathumthanee 12150, Thailand.

Tel : +662-533-2533, +662-994-5199

Fax : +662-533-2449, +662-994-5180



www.chaiyaboon.com

e-mail : exportmarketing@chaiyaboon.com

Storage

- Screenstrip Paste be stored in a cool dry place at 0 – 35 °C.
- SST007 can be stored for 24 months.



CHAIYABOON
— inKnovation —