



TEXTO INK (TO)

Main Characteristics

Ink Type

One Pack – Water Based

Drying

- Jet dry : 3–5 minutes
- Air dry : 24 hours
- Final step oven : 140–150 °C 1–3 minutes

Thinning

- 5–10% Water

Cleaning

- Water
- For heavy ink stains, Screensolve (SSO038) can be used.

Mesh

- P36–90 to P77–55 Monofilament

Stencil Type

- All water-resistant direct Emulsion photo-stencils

Recommended

- T326 Diazol Tex
- FT426 Polyzol Tex

Application

- Light shade fabrics made wholly or partly of natural fibres such as cotton

Important

- Stir well before use.
- It is advisable that the ink be tested fully prior to printing.

Colours Range

24 Colours : 15 Standard, 5 Fluorescent and 4 Trichromatic colours

Features

- Suitable for light shade fabrics made wholly or partly of natural fibres such as cotton.
- Long lasting colour brightness.
- Excellent wash resistance.

Available Colours

Standard Colours

TO100 Black	TO347 Mid Chrome	TO623 Mid Blue	TO721 Bright Green
TO200 White	TO400 Light Orange	TO624 Royal Blue	TO791 Light Brown
TO330 Light Chrome	TO520 Scarlet	TO645 Navy Blue	TO861 Gold
TO340 Mid Chrome	TO590 Violet	TO720 Brilliant Green	TO090 Clear

Fluorescent Colours

TF381 Fluorescent Yellow	TF581 Fluorescent Red	TF582 Fluorescent Pink	TF781 Fluorescent Green
TF482 Fluorescent Orange			

Trichromatic Colours

TO110 Trichromatic Black	TO310 Trichromatic Yellow	TO510 Trichromatic Magenta	TO610 Trichromatic Cyan
--------------------------	---------------------------	----------------------------	-------------------------

CHAIYABOON BROTHERS CO.,LTD.

Head Office Pathumthanee 26/9 M.3 Lamlukka Rd, Lamlukka, Pathumthanee 12150, Thailand.

Tel : +662-533-2533, +662-994-5199

Fax : +662-533-2449, +662-994-5180

www.chaiyaboon.com

e-mail : exportmarketing@chaiyaboon.com



รางวัลอภยบรรณดีเด่น พหุการค้าไทย



Standard Packing

50 Kg, 25 Kg, 3.5 Kg, 1 Kg and 500 g container.

Safety and Handling

- All colours comply with the following standards : EN71-3, Standard of The European Economic Community and Part1303, Title16, Code of Federal Regulation of U.S.A.
- Whilst working with the ink, the consumption of food and drink, and smoking are not recommended.
- TO ink should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Comprehensive information on **the Safety and Handling of TO ink** in Safety Data Sheet, available on request.

Storage

- TO ink should be stored in a sealed container between 5-25 °C.
- Store in a well ventilated place.



TO 3-1902

The information and recommendations contained in this Product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and or condition that users shall make their own tests to satisfy themselves that they will meet fully their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product information sheet out of date and users are requested to ensure that they follow current recommendations.