



BALLOON – BAL INK (BAL)

Main Characteristics

Finish

Semi – Gloss

Ink Type

One Pack – Solvent Based

Drying

- Air dry : Not over 5 minutes

Thinning

- 5-10 % Thinner 2956

Cleaning

- Cleaner 2940
- For heavy ink stains, Screensolve (SSO038) can be used.

Mesh

- P90-40 Monofilament

Stencil Type

- All solvent-resistant direct Emulsion photo-stencils

Recommended

- U017 Diazol Plus Ultra
- FG226 Polyzol Plus S

Coverage & Mesh No.

- 60 m²/Kg (Polyester Mesh No. P90-40)

Application

- Balloon.

Caution

- Stir well before use.
- It is advisable that the ink be tested fully prior to printing.

Colours Range

11 Colours : 2 Standard and 9 CMS

Features

- Printing onto Balloon.
- Excellent flexibility.
- Fast drying and semi gloss.

Available Colours

Standard Colours

BAL100 Black

BAL200 White

BAL090 Clear

CHAIYABOON BROTHERS CO.,LTD.

Head Office Pathumthanee 26/9 M.3 Lamlukka Rd, Lamlukka, Pathumthanee 12150, Thailand.

Tel : +662-533-2533, +662-994-5199

Fax : +662-533-2449, +662-994-5180

www.chaiyaboon.com

e-mail : exportmarketing@chaiyaboon.com



รางวัลอุตสาหกรรมดีเด่น พหุภาคีไทย



CMS Base Colours

| | | | |
|------------------|---------------|----------------|---------------|
| BAL327 Yellow GS | BAL407 Orange | BAL550 Red BS | BAL590 Violet |
| BAL347 Yellow RS | BAL500 Red YS | BAL560 Magenta | BAL600 Blue |
| | | | BAL700 Green |

Standard Packing

1 Kg container.

Safety and Handling

- All other colours comply with the following standards : EN71-3, Standard of The European Economic Community and Part1303, Title16, Code of Federal Regulation of U.S.A.
- Whilst working with the ink, the consumption of food and drink, and smoking are not recommended.
- BAL ink should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Comprehensive information on **the Safety and Handling of BAL ink** in Safety Data Sheet, available on request.

Storage

- BAL ink should be stored in a sealed container between 5-25 °C.
- Store in a well ventilated place.

BAL 3-1901

The information and recommendations contained in this Product information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and or condition that users shall make their own tests to satisfy themselves that they will meet fully their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product information sheet out of date and users are requested to ensure that they follow current recommendations.