



## DEGREASER PLUS (P-4419)

### Main Characteristics

#### Product Characteristics

Gel/ Light brown colour

#### Instruction for use

- Soak the screen with water.
- Use the soft brush to apply some of the Degreaser plus P-4419 onto the screen mesh and rub in a circular motion.
- With a circular motion, rub into the mesh and ensure the entire screen area is treated.
- Leave for a few minutes.
- Use a strong water jet or high pressure water gun to remove the Degreaser.
- Dry the screen thoroughly before further use.

#### Important

- Stir well before use.

### Features

- For pre-treatment of all mesh used with direct emulsion, capillary and direct/indirect films, on both new and used screens.
- Ensures consistent adhesion, eliminates static, fisheyes and pinholes.
- Easy to operate.

### Standard Packing

25 Kg, 5 Kg and 1 Kg

### Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- P-4419 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Degreaser Plus* in Safety Data Sheet.

### Storage

- Degreaser Plus should be stored in a cool dry place at 20-25 °C.
- P-4419 can be stored for 30 months.

### CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand  
Tel : +662-533-2533, +662-994-5199  
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com  
e-mail : sale\_cb@cbg.in.th



**Certified Standards**

- P-4419 is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.



CHAIYABOON  
— inKnovation —