



FLUORESCENT - PVC INK (FPM)

Main Characteristics

Finish

Matt

Ink Type

One Pack - Solvent Based

Drying

- Air dry : Not over 5-20 minutes (Printing onto soft PVC)
- Air dry : Not over 20-40 minutes (Printing onto rigid PVC)

Thinning

- 5-15 % Thinner 13019
- 5-15 % Fast Thinner 2938
- Please use FPM Inks with only recommended Thinner.

Cleaning

- Cleaner 2940
- For heavy ink stains, Screensolve (SSO038) can be used.

Mesh

- P90-48 to P120-34 Monofilament

Stencil Type

- All solvent-resistant direct Emulsion photo-stencils

Emulsion Recommended

- U017 Diazol Plus Ultra
- FG226 Polyzol Plus S

Coverage & Mesh No.

- 30-35 m²/Kg (Polyester Mesh No. P90-48)

Application

- PVC Plastic, PVC copolymers, Vinyl Coated Paper, CAB, PS, Top-coated Polyester, Acrylic and PC

Important

- Stir well before use.
- It is advisable that the ink be tested fully prior to printing.

Colours Range

4 Colours : 4 Fluorescent colours

Features

- Printing onto PVC Plastic, PVC Copolymers, Vinyl Coated Paper.
- Top-coated Polyester, and most CAB, Polystyrene/PS, Acrylic and Polycarbonates/PC.
- Excellent printability.
- Fast drying.

Available Colours

Fluorescent Colours

FPM381 Fluorescent Yellow

FPM581 Fluorescent Red

FPM582 Fluorescent Orange Pink

FPM583 Fluorescent Pink

Standard Packing


1 Kg container.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
Tel : +662-533-2533, +662-994-5199
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
e-mail : sale_cb@cbg.in.th



Safety and Handling

- All colours comply with the following standards : EN71-3, Standard of The European Economic Community and Part1303, Title16, Code of Federal Regulation of U.S.A.
- Whilst working with the ink, the consumption of food and drink, and smoking are not recommended.
- FPM ink should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Comprehensive information on **the Safety and Handling of FPM ink** in Safety Data Sheet, available on request.

Storage

- FPM ink should be stored in a sealed container between 5-25 °C.
- Store in a well ventilated place.

Certified Standards

- FPM ink is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

