



SCREEN SEALER (22983)

Main Characteristics

Product Characteristics

Viscous/Red colour

Instruction for use

- Use tools to coat the filler onto the connecting part of screen and frame, too thick coating is not allowed, enough drying is needed.
- Good ventilation can make the filler dry quickly.

Features

- Used for blocking out stencil to prevent it from breaking when printing.
- Quick drying, convenient to use.
- Strong water and solvent resistance.
- Good printing resistance.

Notes

- If the paste of screen filler congealed, put the tank of filler into warm water for soaking to make it dissolved. It won't affect the use.
- With irritation, avoid touching the body when using the filler. Keep good ventilation in the operating room.

Standard Packing

1 Kg

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screen Sealer* in Safety Data Sheet.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
Tel : +662-533-2533, +662-994-5199
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
e-mail : sale_cb@cbg.in.th



Storage

- Storage temperature should not be over 25 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 12 months from the date of manufacture.
- Close the bottle tightly after every use.

Certified Standards

- Screen Sealer is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

