



SCREENSTRIP POWDER (SST002)

Main Characteristics

Product Characteristics

Powder/White colour

Instruction for use

- For normal decoating ,mix 100 g of Screenstrip Powder SST002 with 10 liters of water.
- For the decoating of old stencils or those used for long print runs or treated with PATLY, mix 100 g. of Screenstrip Powder SST002 with 5 liters of water.

Stencils can be decoated as follows:

- Ensure that the screen is completely free from ink residues remain, use Screensolve SSO038 to clean the screen.
- Rinse both sides of the screen with water and allow to drain.
- Apply Screenstrip Powder solution to both sides of the screen with a brush.
- Rub into the entire stencil area.
- Leave the screen for a few minutes, but do not allow product to dry.
- Wash the stencil with mains pressure water and then use a high-pressure water gun if required.
- Stubborn stains may require additional treatment with Screensolve SSO038.
- If any ink or stencil stains remain, Screenpaste & Screensolve or Chlorine should be used.
- Before the reclaimed screen is used again, it should be prepared with Degreaser P-6419.

Features

- Can be used on Nylon, Polyester and stainless steel meshes.
- It is supplied as easily diluted powder.

Standard Packing

25 Kg, 1 Kg and 100 g

Safety and Handling

- Is free from any toxic, carcinogenic, mutagenic and reprotoxic chemicals.
- Does not have a flashpoint and is, therefore, exempt from the Highly Flammable Liquid Regulations.
- SST002 should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Should be stored away from children.
- Comprehensive information on *the Safety and Handling of Screenstrip Powder* in Safety Data Sheet.

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
Tel : +662-533-2533, +662-994-5199
Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
e-mail : sale_cb@cbg.in.th



Storage

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- Close the bottle tightly after every use.

Certified Standards

- SST002 is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.



CHAIYABOON
— inKnovation —