



TEXTO INK (TO)

Main Characteristics

Ink Type

One Pack / Water-Based

Drying

- Jet dry : 3-5 minutes
- Air dry : 24 hours
- Final step oven : 140-150 °C 1-3 minutes

Thinning

- 5-10% Water

Cleaning

- Water
- For heavy ink stains, Screensolve (SSO038) can be used.

Mesh

- P36-90 to P77-55 Monofilament

Stencil Type

- All water-resistant direct Emulsion photo-stencils

Recommended

- T326 Diazol Tex
- FT426 Polyzol Tex

Application

- Light shade fabrics made wholly or partly of natural fibres such as cotton

Important

- Stir well before use.
- It is advisable that the ink be tested fully prior to printing.

Colours Range

24 Colours : 15 Standard, 5 Fluorescent and 4 Trichromatic colours

Features

- Suitable for light shade fabrics made wholly or partly of natural fibres such as cotton.
- Long lasting colour brightness.
- Excellent wash resistance.

Available Colours

Standard Colours

TO100 Black

TO347 Mid Chrome

TO623 Mid Blue

TO721 Bright Green

TO200 White

TO400 Light Orange

TO624 Royal Blue

TO791 Light Brown

TO330 Light Chrome

TO520 Scarlet

TO645 Navy Blue

TO861 Gold

TO340 Mid Chrome

TO590 Violet

TO720 Brilliant Green

TO090 Clear

Fluorescent Colours

TF381 Fluorescent Yellow

TF581 Fluorescent Red

TF582 Fluorescent Pink

TF781 Fluorescent Green

TF482 Fluorescent Orange

Trichromatic Colours

TO110 Trichromatic Black

TO310 Trichromatic Yellow

TO510 Trichromatic Magenta

TO610 Trichromatic Cyan

CHAIYABOON BROTHERS CO., LTD.

26/17 M.3 Lumlukka Road, Lat Sawai, Lumlukka, Pathum Thani 12150 Thailand
 Tel : +662-533-2533, +662-994-5199
 Fax : +662-994-2449, +662-994-5180

SUPERB SUPPLIES SERVICE FOR SCREEN AND DIGITAL

www.chaiyaboon.com
 e-mail : sale_cb@cbg.in.th



Standard Packing

50 Kg, 25 Kg, 3.5 Kg, 1 Kg and 500 g container.

Safety and Handling

- All colours comply with the following standards : EN71-3, Standard of The European Economic Community and Part1303, Title16, Code of Federal Regulation of U.S.A.
- Whilst working with the ink, the consumption of food and drink, and smoking are not recommended.
- TO ink should be used with care. Wear suitable PPE, for example, appropriate gloves and safety glasses.
- Comprehensive information on **the Safety and Handling of TO ink** in Safety Data Sheet, available on request.

Storage

- Storage temperature should not be over 40 °C. It should be stored in a dry location with good ventilation and away from heat or ignition sources.
- When stored under these conditions, It is expected to have a shelf-life of 24 months from the date of manufacture.
- Close the bottle tightly after every use.

Certified Standards

- TO ink is made by Kulwong Co., Ltd. with ISO 9001/ISO 14001/BS OHSAS 18001 & TIS 18001 Certified by TUV NORD (Thailand) Ltd.

